




LISTINGS




Wet
Location

DIMENSIONS—TRIM



1.55" [40mm]


Ø 3.375" [86mm] Aperture



Ø 3.72" [95mm]

Ø 3.375" [86mm]

DIMENSIONS—LIGHT ENGINE



Ø 2.2" [56mm]

Contortionist™

4-114-TL | Premium LED

Trimless Round Wall Wash

Our Contortionist™ series of hot adjustables twist & turn in ways you'll need to see to believe. These dual axis marvels of flexibility can tilt and rotate with minimal light cutoff - which means - you can aim light precisely where it's needed. Engineered as a three piece system, the trim, light engine, and housing configures to specific lighting needs.

FEATURES

Trim

- Ø 3.375" [86mm] Aperture
- Die-cast aluminum trim
- Wet location listed
- Ideal spacing 24" on center and 24" away from the wall

Light Engine

- Anodized black heat sink and media holder

Housings

- Rated for insulated. Non-insulated & Chicago plenum ceilings

PERFORMANCE SUMMARY—STANDARD DIMMING

Color Accuracy (SDCM)	≤ 1 × 2	
L70 Estimate (h)	50,000	
Color Rendering (CRI)	83	98
Lumen Series	3	
Source Lumens	1000	700
LED Wattage	10	9
Lumen Series	5	
Source Lumens	1500	1000
LED Wattage	14	12
Lumen Series	7	
Source Lumens	2000	1300
LED Wattage	20	17



Trimless Round Wall Wash

TAG TYPE



ORDER FORM

1	2	3	4	5

1. TRIM

4-114-TL

Trimless Round Wall Wash Downlight

2. REFLECTOR FINISH

01 White

04 Black

05 Matte Silver

06 Bronze

11 Matte Nickel

CC Custom Color¹

3. MODULE & BEAM SPREAD

4-XTM40 40° Beam

4. COLOR TEMPERATURE

27 2700K

30 3000K

35 3500K

40 4000K

BM27 Beauty 2700K²

VB30 Vibrant 3000K

5. CRI, LUMENS, SERIES

8310 83 CRI, 1000lm, 3 Series

9807 98 CRI, 700lm, 3 Series

8315 83 CRI, 1500lm, 5 Series

9810 98 CRI, 1000lm, 5 Series

8320 83 CRI, 2000lm, 7 Series

9813 98 CRI, 1300lm, 7 Series







NOTES

1 CC custom color requires factory consultation.

2 BM27 beauty color temperature is only available in 98 CRI.

SPECIFICATIONS


COLOR TEMPERATURES

-  2700K
-  2700K Beauty
-  3000K
-  3000K Vibrant
-  3500K
-  4000K

REFLECTOR FINISHES

-  White
-  Black
-  Matte Silver
-  Bronze
-  Matte Nickel


BEAM SPREADS



COMPATIBLE HOUSINGS


NON-INSULATED/FRAME IN

L4X-F-RA (Round Adjustable)
3, 5, 7 Series
L 13.75" W 9.75" H 5.5"
L 350mm W 248mm H 140mm




INSULATED AIRTIGHT

L4X-IC1A-RA (Round Adjustable)
3, 5 Series
L 21.125" W 9.75" H 5.75"
L 537mm W 248mm H 146mm




CHICAGO PLENUM

L4X-CP-RA (Round Adjustable)
3, 5 Series
L 13.625" W 10.875" H 5.5"
L 346mm W 276mm H 140mm



NON-INSULATED EMERGENCY

L4X-FEM-RA (Round Adjustable)
3, 5, 7 Series
L 13.75" W 10.875" H 5.5"
L 350mm W 277mm H 140mm



CERTIFICATIONS

