

LED PIPE™

3" Surface | Premium LED

Our LED Pipe™ family of cylinders provide architects and lighting designers with almost limitless design possibilities. Whether you need to light a space with inaccessible ceilings, disappear among the pipes and ducts of an open-ceiling design, focus attention on a specific architectural detail or make a dramatic statement, you can solve almost any lighting problem with a LED Pipe™.



Downlight



OPTIONAL ACCESSORIES



**SYMMETRICAL
SNOOT**



**ASYMMETRICAL
SNOOT**



**SYMMETRICAL
FROSTED ACRYLIC**



**SYMMETRICAL
FROSTED ACRYLIC**

LED PIPE™

3" Surface | Premium LED

RATINGS



Damp
Location



Wet
Location



California
Title 24 JA8

CERTIFICATIONS



Intertek



5yr. Warranty

FEATURES

- Utilizes 97 CRI, 2-step Ellipse, R9 \geq 80 LED
- \varnothing 2 5/8" [67mm] aperture
- 65° tilt from nadir (adjustable surface)
- 350° rotation (adjustable surface)
- Wall Wash optic with 360° rotation adjustment
- Single media ready
- Clear media lens (damp location)
- Clear flush mounted lens (wet location)
- Field interchangeable beam spreads (damp location)
- Extruded aluminum cylinder body
- Machined aluminum components
- Powder coated finishes

FINISHES



Anthracite
Metallic



Chocolate
Metallic



Glimmer
Gold



Ink Black
Metallic



Moroccan
Metallic



Nano
White



Sienna
Metallic



Slate Grey
Metallic

BEAM SPREADS



20°



30°



40°



60°



70°



80°



Wall Wash


COLOR TEMPERATURES



2700K



3000K



3500K

PERFORMANCE SUMMARY (PER LAMP)

Color Accuracy (SDCM)	<2
L70 Estimate (h)	50,000
Color Rendering (CRI)	97
Lumen Series	9708
Source Lumens	1000
Delivered Lumens	770
LED Wattage	9
Lumen Series	9710
Source Lumens	1350
Delivered Lumens	1060
LED Wattage	13
Lumen Series	9714
Source Lumens	1850
Delivered Lumens	1460
LED Wattage	18

- Source lumens are based on 3000K color temperature.
- Delivered lumens are based on 3000K color temperature, 40° beam angle and clear lens.
- Refer to IES files for individual product information.
- Consult factory for additional lower lumen options.

3" Surface | Premium LED | Integral Driver | Order Form

Order Code Example: C3S-R-W-6-21-21-X20-27-9710-S-120-3C-FR-S1-21

PRODUCT NOTES:

1. Not available with wet location.
2. [Blank] clear media lens mounted to regressed trim aperture.
3. W clear glass lens is flush mounted to the trim aperture and is wet location listed when selected. Not available with XWW Beam Spread.
4. Field interchangeable beam spread options require consultation with Lightheaded personnel.
5. XWW wall wash optic is aimable after installation.
6. LH, P1, P0 and D dimming require Large ceiling canopy. Refer to dimensional data.
7. 120 volt is only available in S dimming
8. UNV volt is only available in P & LH dimming
9. 347 Volt is only available in P (0-10V) dimming with 5C mounting option.
10. 3C ceiling canopy includes C3-R-3CMP junction box mounting plate. (can be shipped in advance upon request). Must be installed with octagonal junction box prior to ceiling installation. Octagonal junction box not included.
11. 3C mounting is only available with P (0-10V) or S (phase) dimming
12. CM mounts over 4" octagonal junction box (by others). Comes with 2 conduit feed covers & 3 blank covers. Consult factory for additional conduit accessories.
13. CM is not available with 3C mounting.
14. Athena Wireless node is only in P (0-10V) and D (Dali 2) dimming
15. Athena Wireless node is not available in 3C mounting.
16. Optional media replaces clear media when selected. Not available with XWW wall wash.
17. Accessories are not available with wet location option.
18. Finish required for S1 & S2 snoots.

Wet Location

Title 24 JA8 qualified, consult factory for complete listing.

SELECT A CYLINDER

[1] CYLINDER

- C3S** 3" Fixed Surface ●
- C3SA** 3" Adjustable Surface ●¹

[2] CYLINDER SHAPE

- R** Round

[3] GLASS

- [Blank]** Clear Lens²
- W** Clear Lens ●³

[4] LAYOUT

- 6** 6" Cylinder Length
- 9** 9" Cylinder Length

[5] FINISH

- 21** Nano White
- 23** Anthracite Metallic
- 24** Ink Black Metallic
- 25** Slate Grey Metallic
- 28** Glimmer Gold
- 31** Sienna Metallic
- 32** Moroccan Metallic
- 34** Chocolate Metallic
- CC** Custom Color

[6] REFLECTOR FINISH

- 21** Nano White
- 23** Anthracite Metallic
- 24** Ink Black Metallic
- 25** Slate Grey Metallic
- 28** Glimmer Gold
- 31** Sienna Metallic
- 32** Moroccan Metallic
- 34** Chocolate Metallic
- CC** Custom Color

[7] MODULE & BEAM SPREAD⁴

- X20** 20° Beam
- X30** 30° Beam
- X40** 40° Beam
- X60** 60° Beam
- X70** 70° Beam
- X80** 80° Beam
- XWW** Wall Wash⁵

[8] COLOR TEMPERATURE

- 27** 2700K
- 30** 3000K
- 35** 3500K

[9] LUMENS SERIES

- 9708** 97 CRI, 1000lm ●
- 9710** 97 CRI, 1350lm ●
- 9714** 97 CRI, 1850lm ●

[10] DIMMING⁷

- S** Phase Dimming (1%)
- P** 0-10V Dimming (1%)
- P1** 0-10V eldoLED ECOdrive (1%)⁶
- P0** 0-10V eldoLED SOLOdrive (0.1%)⁶
- D** Dali-2 eldoLED ECOdrive (1%)⁶
- LH** Lutron Hi-lume EcoSystem Soft-on Fade-to-Black (1%)⁶

[11] VOLTAGE

- 120** 120V⁷
- UNV** 120-277V⁸
- 347** 347V⁹

[12] MOUNTING

- 3C** 3" Ceiling Canopy (Includes C3-R-3CMP Mounting Plate)^{10,11}
- 5C** 5" Ceiling Canopy

[13] OPTIONS

- CM** Conduit mount to surface mount 4" octagonal junction box^{1,12,13}
- AW** Lutron Athena Wireless Node RF only^{14,15}

[14] OPTIONAL MEDIA (1 MAX.)¹⁶

- [Blank]** No Media
- FR** Frosted
- HC** Honeycomb
- PF** Perimeter Frosted
- SL** Softening
- SPDL** Spread

[15] OPTIONAL ACCESSORIES¹⁷

- S1** Snoot Symmetric (1.25")¹⁸
- S2** Snoot Asymmetric (1.5")¹⁸
- A1** Frosted Acrylic Trim (0.5")
- A2** Frosted Acrylic Trim (2.0")

[16] ACCESSORIES FINISH¹⁸

- 21** Nano White
- 23** Anthracite Metallic
- 24** Ink Black Metallic
- 25** Slate Grey Metallic
- 28** Glimmer Gold
- 31** Sienna Metallic
- 32** Moroccan Metallic
- 34** Chocolate Metallic
- CC** Custom Color

3" Surface | Premium LED | Remodel Driver | Order Form

Order Code Example: C3S-R-W-6-21-21-X20-27-9710-RM-3C-FR-S1-21-DRX-C3-3-S-UNV

PRODUCT NOTES:

1. Not available with wet location.
2. Not available in 9" cylinder length
3. [Blank] clear media lens mounted to regressed trim aperture.
4. W clear glass lens is flush mounted to the trim aperture and is wet location listed when selected. Not available with XWW Beam Spread.
5. Field interchangeable beam spread options require consultation with Lighthheaded personnel.
6. XWW wall wash optic is aimable after installation.
7. RM remodel driver sold separately.
8. Optional media replaces clear media when selected. Not available with XWW wall wash.
9. Accessories are not available with wet location option.
10. Finish required for S1& S2 snoots.
11. 120 volt is only available in S dimming.
12. UNV volt is only available in P & LH dimming.
- Title 24 JA8 qualified, consult factory for complete listing.

SELECT A CYLINDER

[1] CYLINDER

- C3S** 3" Fixed Surface ●
- C3SA** 3" Adjustable Surface ●^{1,2}

[2] CYLINDER SHAPE

- R** Round

[3] GLASS

- [Blank]** Clear Lens³
- W** Clear lens ●⁴

[4] LAYOUT

- 6** 6" Cylinder Length
- 9** 9" Cylinder Length

[5] FINISH

- 21** Nano White
- 23** Anthracite Metallic
- 24** Ink Black Metallic
- 25** Slate Grey Metallic
- 28** Glimmer Gold
- 31** Sienna Metallic
- 32** Moroccan Metallic
- 34** Chocolate Metallic
- CC** Custom Color

[6] REFLECTOR FINISH

- 21** Nano White
- 23** Anthracite Metallic
- 24** Ink Black Metallic
- 25** Slate Grey Metallic
- 28** Glimmer Gold
- 31** Sienna Metallic
- 32** Moroccan Metallic
- 34** Chocolate Metallic
- CC** Custom Color

[7] MODULE & BEAM SPREAD⁵

- X20** 20° Beam
- X30** 30° Beam
- X40** 40° Beam
- X60** 60° Beam
- X70** 70° Beam
- X80** 80° Beam
- XWW** Wall Wash⁶

[8] COLOR TEMPERATURE

- 27** 2700K
- 30** 3000K
- 35** 3500K

[9] LUMENS SERIES

- 9708** 97 CRI, 1000lm ●
- 9710** 97 CRI, 1350lm ●
- 9714** 97 CRI, 1850lm ●

[10] DIMMING

- RM** Remodel Driver⁷

[11] MOUNTING

- 3C** 3" Ceiling Canopy

[12] OPTIONAL MEDIA (1 MAX.)⁸

- FR** Frosted
- HC** Honeycomb
- PF** Perimeter Frosted
- SL** Softening
- SPDL** Spread

[13] OPTIONAL ACCESSORIES⁹

- S1** Snoot Symmetric (1.25")¹⁰
- S2** Snoot Asymmetric (1.5")¹⁰
- A1** Frosted Acrylic Trim (0.5")
- A2** Frosted Acrylic Trim (2.0")

[14] ACCESSORIES FINISH¹⁰

- 21** Nano White
- 23** Anthracite Metallic
- 24** Ink Black Metallic
- 25** Slate Grey Metallic
- 28** Glimmer Gold
- 31** Sienna Metallic
- 32** Moroccan Metallic
- 34** Chocolate Metallic
- CC** Custom Color

[15] DRIVER TYPE

- DRX-C3** Remodel Driver

[16] LUMENS SERIES

- 2** 1000 Lumens Max (9708)
- 3** 1350 Lumens Max (9710)
- 5** 1850 Lumens Max (9714)


[17] DIMMING

- LH** Lutron Hi-lume EcoSystem
- Soft-on Fade-to-Black (1%)
- P** 0-10V Dimming (10%)
- S** Phase Dimming (10%)

[18] VOLTAGE


- 120** 120V¹¹
- UNV** 120-277V¹²

SMALL CEILING CANOPY (FIXED & WALL WASH CYLINDER)




INTEGRAL DRIVER (P, S DIMMING)

FINISHED INSTALL



CANOPY ASSEMBLY




Note: Junction box mounting plate must be installed prior to the ceiling installation. Can be shipped in advance upon request.


Note: Junction box not included.

REMODEL DRIVER (LH, P, S DIMMING)


FINISHED INSTALL



REMODEL DRIVER




CANOPY ASSEMBLY



Note: Remodel driver sold separately.


LARGE CEILING CANOPY (FIXED & WALL WASH CYLINDER)



	Dimming					
	P	S	D	LH	P1	P0
Canopy Diameter	Ø 4.75" [Ø 121mm]		Ø 5.75" [Ø 146mm]			
Canopy Height	0.25" [7mm]		2" [51mm]			


INTEGRAL DRIVER

FINISHED INSTALL




Note: Junction box not included.

CANOPY ASSEMBLY
(D, LH, P1, P0 DIMMING)




CANOPY ASSEMBLY
(P, S DIMMING)




SMALL CEILING CANOPY (ADJUSTABLE CYLINDER)

Canopy Diameter




INTEGRAL DRIVER (P, S DIMMING)

FINISHED INSTALL



CANOPY ASSEMBLY





Note: Junction box mounting plate must be ordered and installed prior to the ceiling installation.


Note: Junction box not included.

REMODEL DRIVER (LH, P, S DIMMING)

FINISHED INSTALL




REMODEL DRIVER



Note: Remodel driver sold separately.


LARGE CEILING CANOPY (ADJUSTABLE CYLINDER)



	Dimming					
	P	S	D	LH	P1	P0
Canopy Diameter	Ø 4.75" [Ø 121mm]		Ø 5.75" [Ø 146mm]			
Canopy Height	0.25" [7mm]		2" [51mm]			

INTEGRAL DRIVER


FINISHED INSTALL (D, LH, P1, P0)




Note: Junction box not included.

Note: Junction box not included.
*Consult factory for 1 1/2" deep Junction Box option.


CANOPY ASSEMBLY (D, LH, P1, P0 DIMMING)



FINISHED INSTALL (P, S)



CANOPY ASSEMBLY (P, S DIMMING)




CONDUIT MOUNT CEILING CANOPY (FIXED & WALL WASH DOWNLIGHT CYLINDER)

SURFACE CONDUIT MOUNT TO 4" OCTAGONAL JUNCTION BOX WITH CONDUIT ENTRY


(D, LH, P1)

Ø 5.75" [146mm]




(P, S)

Ø 5.75" [146mm]




INTEGRAL DRIVER

FINISHED INSTALL (D, LH, P1, P0)




FINISHED INSTALL (P, S)




Note: Junction box not included.

CANOPY ASSEMBLY (D, LH, P1, P0 DIMMING)




CANOPY ASSEMBLY (P, S DIMMING)




CONDUIT ACCESSORIES

FEED COVER BLANK COVER



4" OCTAGONAL JUNCTION BOX (BY OTHERS)




CONDUIT MOUNT CEILING CANOPY (ADJUSTABLE CYLINDER)

SURFACE CONDUIT MOUNT TO 4" OCTAGONAL JUNCTION BOX WITH CONDUIT ENTRY


(D, LH, P1)

Ø 5.75" [146mm]




(P, S)

Ø 5.75" [146mm]




INTEGRAL DRIVER

FINISHED INSTALL (D, LH, P1)




FINISHED INSTALL (P, S)




Note: Junction box not included.

CANOPY ASSEMBLY (D, LH, P1 DIMMING)




CANOPY ASSEMBLY (P, S DIMMING)




CONDUIT ACCESSORIES

FEED COVER BLANK COVER





4" OCTAGONAL JUNCTION BOX (BY OTHERS)




SNOOT ACCESSORIES (PENDANT CYLINDER)


SYMMETRICAL SNOOT (S1)





PENDANT WITH SYMMETRICAL SNOOT INSTALLED




ADJUSTABLE PENDANT WITH SYMMETRICAL SNOOT INSTALLED




ASYMMETRICAL SNOOT (S2)



PENDANT WITH ASYMMETRICAL SNOOT INSTALLED





ADJUSTABLE PENDANT WITH ASYMMETRICAL SNOOT INSTALLED




DECORATIVE TRIMS ACCESSORIES (PENDANT CYLINDER)


FROSTED ACRYLIC TRIM (A1)





PENDANT WITH FROSTED ACRYLIC TRIM INSTALLED




ADJUSTABLE PENDANT WITH FROSTED ACRYLIC TRIM INSTALLED



FROSTED ACRYLIC TRIM (A2)



PENDANT WITH FROSTED ACRYLIC TRIM INSTALLED



ADJUSTABLE PENDANT WITH FROSTED ACRYLIC TRIM INSTALLED

